

INSTALLAZIONE – INSTALLATION  
MONTAGE – INSTALACION

Diagram A shows the overall assembly. A horizontal bar of length 770 mm is mounted on a wall. A central component A is attached to the bar. A bracket B is used to secure the bar to the wall. The bracket has a height of 85 mm and a width of 40 mm. The bar is secured with two screws, each with a diameter of 6 mm.

| PART LIST |      |
|-----------|------|
| Rif.      | Q.tà |
| A         | 1    |
| B         | 1    |

Diagram B provides a detailed view of the bracket B. It shows the internal components, including a screw and a washer. The bracket is secured to the wall with a screw. The application of silicone sealant is shown at the junction of the bracket and the wall. The dimensions 2.5 mm and 2 mm are indicated for the sealant application.

Diagram C shows a detailed view of the bracket B. It illustrates the internal components, including a screw and a washer. The bracket is secured to the wall with a screw. The application of silicone sealant is shown at the junction of the bracket and the wall. The dimensions 2.5 mm and 2 mm are indicated for the sealant application.

Diagram D shows a detailed view of the bracket B. It illustrates the internal components, including a screw and a washer. The bracket is secured to the wall with a screw. The application of silicone sealant is shown at the junction of the bracket and the wall. The dimensions 2.5 mm and 2 mm are indicated for the sealant application.

Diagram E shows a detailed view of the bracket B. It illustrates the internal components, including a screw and a washer. The bracket is secured to the wall with a screw. The application of silicone sealant is shown at the junction of the bracket and the wall. The dimensions 2.5 mm and 2 mm are indicated for the sealant application.

Diagram F shows a detailed view of the bracket B. It illustrates the internal components, including a screw and a washer. The bracket is secured to the wall with a screw. The application of silicone sealant is shown at the junction of the bracket and the wall. The dimensions 2.5 mm and 2 mm are indicated for the sealant application.